Indiana Department of Environmental Management



We make Indiana a cleaner, healthier place to live.

Governor

Lori F. Kaplan Commissioner

6015

100 North Senate AvenueP. O. Box 6015Indianapolis, Indiana 46206-

(317) 232-8603 (800) 451-6027 www.state.in.us/idem

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) Renewal OFFICE OF AIR QUALITY

Swiss Plywood Corp. 102 Main Street Tell City, Indiana 47586

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: F123-15136-00007	
Issued by:Original signed by Paul Dubenetzky Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date:February 4, 2003 Expiration Date:February 4, 2008

 Swiss Plywood Corp.
 Page 2 of 35

 Tell City, Indiana
 OP No. F123-15136-00007

Permit Reviewer: AY	//EVP
---------------------	-------

SECTIO	N A	SOURCE SUMMARY
	A.1	General Information [326 IAC 2-8-3(b)]
	A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]
	A.3	Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]
	A.4	FESOP Applicability [326 IAC 2-8-2]
	A.5	Prior Permits Superseded [326 IAC 2-1.1-9.5]
SECTIO	N B	GENERAL CONDITIONS 6
	B.1	Permit No Defense [IC 13]
	B.2	Definitions [326 IAC 2-8-1]
	B.3	Permit Term [326 IAC 2-8-4(2)]
	B.4	Enforceability [326 IAC 2-8-6]
	B.5	Termination of Right to Operate [326 IAC 2-8-9][326 IAC 2-8-3 (h)]
	B.6	Severability [326 IAC 2-8-4(4)]
	B.7	Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]
	B.8	Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)]
	B.9	Compliance Order Issuance [326 IAC 2-8-5(b)]
	B.10	Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]
	B.11	Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]
	B.12	Annual Compliance Certification [326 IAC 2-8-5(a)(1)]
	B.13	Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)][326 IAC 2-8-5(a)(1)]
	B.14	Emergency Provisions [326 IAC 2-8-12]
	B.15	Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]
	B.16	Permit Modification, Reopening, Revocation and Reissuance, or Termination
	B.17	Permit Renewal [326 IAC 2-8-3(h)]
	B.18	Permit Amendment or Revision [326 IAC 2-8-10][326 IAC 2-8-11.1]
	B.19	Operational Flexibility [326 IAC 2-8-15] [326 IAC 2-8-11.1]
	B.20	Permit Revision Requirement [326 IAC 2-8-11.1]
	B.21	Inspection and Entry [326 IAC 2-8-5(a)(2)] [I13-14-2-2]
	B.22	Transfer of Ownership or Operation [326 IAC 2-8-10]
	B.23	Annual Fee Payment [326 IAC 2-8-4(6)] [326 IAC 2-8-16]
SECTIO	N C	SOURCE OPERATION CONDITIONS
	Emissi	on Limitations and Standards [326 IAC 2-8-4(1)]
	C.1	Overall Source Limit [326 IAC 2-8]
	C.2	Particulate Emission Limitations For Processes with Process Weight Rates Less Than
		One Hundred (100) pounds per hour [40 CFR 52 Subpart P][326 IAC 6-3-2]
	C.3	Opacity [326 IAC 5-1]
	C.4	Open Burning [326 IAC 4-1][IC 13-17-9]
	C.5	Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]
	C.6	Fugitive Dust Emissions [326 IAC 6-4]
	C.7	Operation of Equipment [326 IAC 2-8-5(a)(4)]
	C.8	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]
	Testing C.9	Requirements [326 IAC 2-8-4(3)] Performance Testing [326 IAC 3-6]
	Compli	ance Requirements [326 IAC 2-1.1-11]
	C.10	Compliance Requirements [326 IAC 2-1.1-11]
		ance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]
	C.11	Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]
	C.12	Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]
	C.13	Pressure Gauge Specifications

Swiss Plywood Corp.	Page 3 of 3
Fell City, Indiana	OP No. F123-15136-0000

Tell City, I Permit Re		OP No. F123-15136-00007 Y/EVP
	C.14	Risk Management Plan [326 IAC 2-8-4] [40 CFR 68.215]
	C.15	Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-8-4] [326 IAC 2-8-5]
	C.16	Actions Related to Noncompliance Demonstrated by a Stack Test
		Keeping and Reporting Requirements [326 IAC 2-8-4(3)]
	C.17	Emission Statement [326 IAC 2-6] [326 IAC 2-8-4(3)]
	C.18 C.19	General Record Keeping Requirements [326 IAC 2-8-4(3)][326 IAC 2-8-5] General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]
		pheric Ozone Protection
	C.20	Compliance with 40 CFR 82 and 326 IAC 22-1
		FACILITY OPERATION CONDITIONS one (21) Spray paint booths
		on Limitations and Standards [326 IAC 2-8-4(1)]
		Volatile Organic Compounds (VOC) [326 IAC 2-8-4][326 IAC 2-2][40 CFR 52.21]
		Hazardous Air Pollutants (HAPs) [326 IAC 2-8-4]
		Particulate-Matter (PM) [40 CFR 52 Subpart P]
	D.1.4	Preventive Maintenance Plan [326 IAC 2-8-4(9)]
	Compli	ance Determination Requirements
	D.1.5	Volatile Organic Compounds (VOC) and Hazardous Air Pollutants (HAPs)
	D.1.6	VOC and HAP Emissions
	Compli	ance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]
	D.1.7	Particulate [326 IAC 6-3-2(d)]
	D.1.8	Monitoring
	Record	Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]
	D.1.9	Record Keeping Requirements
	D.1.10	Reporting Requirements
		FACILITY OPERATION CONDITIONS vorking operations
		on Limitations and Standards [326 IAC 2-8-4(1)]
	D.2.1	Particulate [326 IAC 6-3-2]
	D.2.2	PM10 Emission Limitation [326 IAC 2-8-4]
	D.2.3	Preventive Maintenance Plan [326 IAC 2-8-4(9)]
		ance Determination Requirements Particulate Control
	Compli	ance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]
	D.2.5	Visible Emissions Notations
	D.2.6	Baghouse Inspections
	D.2.7	Broken or Failed Bag Detection
	Record D.2.8	Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16] Record Keeping Requirements
Certific	ation Fo	orm
Emerge	ncy Oc	currence Form
		t Form

Page 4 of 35 OP No. F123-15136-00007

Swiss Plywood Corp. Page 5 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-8-3(b)]

The Permittee owns and operates a stationary wood furniture and cabinet manufacturing plant.

Authorized individual: William Borders, President

Source Address: 102 Main Street, Tell City, Indiana 47586 Mailing Address: 102 Main Street, Tell City, Indiana 47586

General Source Phone: (812) 547-2366

SIC Code: 2434, 2511, 2517 and 2599

County Location: Perry

Source Location Status: Attainment for all criteria pollutants

Federally Enforceable State Operating Permit (FESOP)

Minor Source, under PSD Rules

Minor Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

This stationary source consists of the following emission units and pollution control devices:

- (a) Twenty-one (21) spray paint booths identified as E1, E2, E3, E5, E6, E7, E9, E10, E11, E13, E14, E15, E17, E19, E20, E21, E23, E24, E25, E26 and E28 (each constructed prior to 1974). Each booth is equipped with conventional air spray guns, HVLP spray guns, and air-assisted airless spray guns for wood furniture coating, and is equipped with dry filters for particulate matter control, and each exhausting through stacks identified as following: S1 and S2 for E1; S3 and S4 for E2; S5 S7 for E3; S10 and S11 for E5; S12 and S13 for E6; S41 for E7; S17 and S18 for E9; S19 and S20 for E10; S21 and S22 for E11; S24 and S25 for E13; S26 for E14; S28 and S29 for E15; S31 and S32 for E17; S16 for E19; S34 for E20; S33 for E21; S35 for E23; S36 for E24; S37 for E25; S40 for E26; and S39 for E28.
- (b) One (1) woodworking operation identified as E22 with a maximum throughput of 4200 pounds per hour of wood, equipped with two (2) baghouses (identified as E22a & E22b) for particulate matter control and exhausting through stacks S38a and S38b, respectively.

A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]

This stationary source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Vessels storing lubricating oils, hydraulic oils, machining oils, and machining fluids;
- (b) Filling drums, pails or other packaging containers with lubricating oils, waxes, and greases.
- (c) Cleaners and solvents characterized as follows:

Swiss Plywood Corp. Tell City, Indiana

Permit Reviewer: AY/EVP

Page 6 of 35 OP No. F123-15136-00007

- (1) having a vapor pressure equal to or less than 2 kPa, measured at 38°C, or
- (2) having a vapor pressure equal to or less than 0.7 kPa, measured at 20°C.
- (d) Water based adhesives that are less than or equal to 5% by volume of VOCs excluding HAPs.
- (e) Replacement or repair of electrostatic precipitators, bags in baghouses and filters in other air filtration equipment.
- (f) Paved and unpaved roads and parking lots with public access.
- (g) Purging of gas lines and vessels that is related to routine maintenance and repair of buildings, structures, or vehicles at the source where air emissions from those activities would not be associated with any production process.
- (h) Natural gas fired combustion sources with heat input equal to or less than 10 million British thermal units per hour: Five (5) natural gas fired heating ovens, identified as E4, E8, E12, E16 and E18, each rated at maximum heat input rate of 2.30 MMBtu/hr.

A.4 FESOP Applicability [326 IAC 2-8-2]

This stationary source, otherwise required to have a Part 70 permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) to renew a Federally Enforceable State Operating Permit (FESOP).

A.5 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either
 - (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted

by this permit.

(b) All previous registrations and permits are superseded by this permit.

SECTION B GENERAL CONDITIONS

B.1 Permit No Defense [IC 13]

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

B.2 Definitions [326 IAC 2-8-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2, and 326 IAC 2-7) shall prevail.

B.3 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

B.4 Enforceability [326 IAC 2-8-6]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

B.6 Severability [326 IAC 2-8-4(4)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]

This permit does not convey any property rights of any sort, or any exclusive privilege.

B.8 Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)] [326 IAC 2-8-5(a)(4)]

(a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(b) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also

Permit Reviewer: AY/EVP

furnish to IDEM, OAQ, copies of records required to be kept by this permit.

(c) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1 When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]

IDEM, OAQ may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

B.10 Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for:
 - (1) Enforcement action;
 - (2) Permit termination, revocation and reissuance, or modification; and
 - (3) Denial of a permit renewal application.
- (b) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
- (c) An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

B.11 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by an authorized individual of truth, accuracy, and completeness. This certification, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) An authorized individual is defined at 326 IAC 2-1.1-1(1).

B.12 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]

(a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management Compliance Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015 Swiss Plywood Corp. Page 9 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

(b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification:
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
 - (5) Such other facts as specified in Sections D of this permit, IDEM, OAQ, may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

B.13 Preventive Maintenance Plan [326 IAC 1-6-3] [326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall-maintain and implement Preventive Maintenance Plans (PMPs), including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the PMPs as necessary to ensure that failure to implement a PMP does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ, . IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) Records of preventive maintenance shall be retained for a period of at least five (5) years. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

Swiss Plywood Corp. Page 10 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

B.14 Emergency Provisions [326 IAC 2-8-12]

(a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-8-12.

- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describes the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone No.: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section) or,

Telephone No.: 317-233-5674 (ask for Compliance Section)

Facsimile No.: 317-233-5967

(5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management Compliance Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(6) The Permittee immediately took all reasonable steps to correct the emergency.

Swiss Plywood Corp. Page 11 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

(c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.

- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
 - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
 - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
 - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

(h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

(a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Swiss Plywood Corp. Page 12 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

(b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a FESOP modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)] The notification by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
 - (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

B.17 Permit Renewal [326 IAC 2-8-3(h)]

(a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, IN 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-8-3]
 - (1) A timely renewal application is one that is:
 - (A) Submitted at least nine (9) months prior to the date of the expiration of this

Swiss Plywood Corp. Page 13 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

permit; and

- (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (2) If IDEM, OAQ upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.
- (c) Right to Operate After Application for Renewal [326 IAC 2-8-9]

 If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as needed to process the application.

B.18 Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

Any such application shall be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(c) The Permittee may implement the administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.19 Operational Flexibility [326 IAC 2-8-15] [326 IAC 2-8-11.1]

- (a) The Permittee may make any change or changes at this source that are described in 326 IAC 2-8-15(b) through (d), without prior permit revision, if each of the following conditions is met:
 - (1) The changes are not modifications under any provision of Title I of the Clean Air Act:
 - (2) Any approval required by 326 IAC 2-8-11.1 has been obtained;
 - (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);

Swiss Plywood Corp. Page 14 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

(4) The Permittee notifies the:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J) 77 West Jackson Boulevard Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

(5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-8-15(b) through (d) and makes such records available, upon reasonable request, to public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-8-15(b)(2), (c)(1), and (d).

- (b) Emission Trades [326 IAC 2-8-15(c)]
 The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).
- (c) Alternative Operating Scenarios [326 IAC 2-8-15(d)]

 The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAQ or U.S. EPA is required.

B.20 Permit Revision Requirement [326 IAC 2-8-11.1]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-8-11.1.

B.21 Inspection and Entry [326 IAC 2-8-5(a)(2)] [IC 13-14-2-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;

Swiss Plywood Corp. Page 15 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

(c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;

- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.22 Transfer of Ownership or Operational Control [326 IAC 2-8-10]

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

The application which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233- 4320 (ask for OAQ, I/M & Billing Section), to determine the appropriate permit fee.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

Emissions Limitations and Standards [326 IAC 2-8-4(1)]

C.1 Overall Source Limit [326 IAC 2-8]

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

- (a) Pursuant to 326 IAC 2-8:
 - (1) The potential to emit any regulated pollutant, except particulate matter (PM), from the entire source shall be limited to less than one-hundred (100) tons per twelve (12) consecutive month period. This limitation shall also satisfy the requirements of 326 IAC 2-2 (PSD);
 - (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per twelve (12) consecutive month period; and
 - (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period.
- (b) Pursuant to 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)), potential to emit particulate matter (PM) from the entire source shall be limited to less than two hundred fifty (250) tons per twelve (12) consecutive month period.
- (c) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided the source's potential to emit does not exceed the above specified limits.
- (d) Section D of this permit contains independently enforceable provisions to satisfy this requirement.

C.2 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P][326 IAC 6-3-2]

- (a) Pursuant to 40 CFR 52 Subpart P, the allowable particulate matter emissions rate from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.
- (b) Pursuant to 326 IAC 6-3-2(e)(2), the allowable particulate emissions rate from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

(a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.

Swiss Plywood Corp. Page 17 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

(b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and in 326 IAC 9-1-2.

C.6 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.7 Operation of Equipment [326 IAC 2-8-5(a)(4)]

Except as otherwise provided by statute, rule or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission unit vented to the control equipment is in operation.

C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

> Indiana Department of Environmental Management Asbestos Section, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) Procedures for Asbestos Emission Control
 The Permittee shall comply with the applicable emission control procedures in 326 IAC 1410-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are
 applicable for any removal or disturbance of RACM greater than three (3) linear feet on
 pipes or three (3) square feet on any other facility components or a total of at least 0.75
 cubic feet on all facility components.
- (f) Indiana Accredited Asbestos Inspector
 The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator,
 prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to
 thoroughly inspect the affected portion of the facility for the presence of asbestos. The
 requirement that the inspector be accredited is federally enforceable.

Testing Requirements [326 IAC 2-8-4(3)]

C.9 Performance Testing [326 IAC 3-6]

(a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the source submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Swiss Plywood Corp. Page 19 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

C.10 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

C.11 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented upon issuance of this permit. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment.

Unless otherwise specified in the approval for the new emissions unit, compliance monitoring for new emission units or emission units added through a permit revision shall be implemented when operation begins.

C.12 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing performed required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63 or other approved methods as specified in this permit.

C.13 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-8-4(3)] [326 IAC 2-8-4(3)] [326 IAC 2-8-4(3)]

- (a) Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent (±2%) of full scale reading.
- (b) Whenever a condition in this permit requires the measurement of a temperature, flow rate, or pH level, the instrument employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent (±2%) of full scale reading.
- (c) The Permittee may request the IDEM, OAQ approve the use of a pressure gauge or other instrument that does not meet the above specifications provided the Permittee can demonstrate an alternative pressure gauge or other instrument specification will adequately ensure compliance with permit conditions requiring the measurement of pressure drop or other parameters.

Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

C.14 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present at a source in more than a threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall submit:

- (a) A compliance schedule for meeting the requirements of 40 CFR 68; or
- (b) As a part of the annual compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP).

Swiss Plywood Corp. Page 20 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

All documents submitted pursuant to this condition shall include the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

C.15 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-8-4] [326 IAC 2-8-5]

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and is comprised of:
 - (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.
 - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
 - (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
 - (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
 - (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, the IDEM, OAQ shall be promptly notified of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
 - (4) Failure to take reasonable response steps shall constitute a violation of the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:
 - (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.

Swiss Plywood Corp. Page 21 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

(4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.

- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.
- (e) The Permittee shall record all instances when response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-8-12 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4] [326 IAC 2-8-5]

- (a) When the results of a stack test performed in conformance with Section C Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The documents submitted pursuant to this condition do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]

C.17 Emission Statement [326 IAC 2-6] [326 IAC 2-8-4(3)]

(a) The Permittee shall submit an emission statement certified pursuant to the requirements of 326 IAC 2-6. This statement must be received in accordance with the compliance schedule specified in 326 IAC 2-6-3 and must comply with the minimum requirements specified in 326 IAC 2-6-4. The submittal should cover the period defined in 326 IAC 2-6-2(8). The statement must be submitted to:

Indiana Department of Environmental Management Technical Support and Modeling Section, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

The emission statement does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(b) The emission statement required by this permit shall be considered timely if the date

Swiss Plywood Corp. Page 22 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

C.18 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]

- (a) Records of all required data, reports and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.19 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

- (a) The source shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "authorized individual" as defined by 326 IAC2-1.1-1(1).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) Reporting periods are based on calendar years.

Stratospheric Ozone Protection

C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

(a) Persons opening appliances for maintenance, service, repair or disposal must comply with the required practices pursuant to 40 CFR 82.156

Swiss Plywood Corp. Page 23 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

(b) Equipment used during the maintenance, service, repair or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.

(c) Persons performing maintenance, service, repair or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]:

(a) Twenty-one (21) spray paint booths identified as E1, E2, E3, E5, E6, E7, E9, E10, E11, E13, E14, E15, E17, E19, E20, E21, E23, E24, E25, E26 and E28 (each constructed prior to 1974). Each booth is equipped with conventional air spray guns, HVLP spray guns, and air-assisted airless spray guns for wood furniture coating, and is equipped with dry filters for particulate matter control, and each exhausting through stacks identified as following: S1 and S2 for E1; S3 and S4 for E2; S5 - S7 for E3; S10 and S11 for E5; S12 and S13 for E6; S41 for E7; S17 and S18 for E9; S19 and S20 for E10; S21 and S22 for E11; S24 and S25 for E13; S26 for E14; S28 and S29 for E15; S31 and S32 for E17; S16 for E19; S34 for E20; S33 for E21; S35 for E23; S36 for E24; S37 for E25; S40 for E26; and S39 for E28.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.1.1 Volatile Organic Compounds (VOC) [326 IAC 2-8-4]

The total input usage of volatile organic compounds (VOC) at the twenty one (21) spray paint booths. including VOC usage for clean-up, shall be limited to less than 96.0 tons per twelve (12) consecutive month period with compliance determined at the end of each month. This usage limit, including the potential to emit for insignificant activities, is required to limit the source-wide potential to emit of VOC to less than 100 tons per year.

Compliance with this limitation shall make the requirements of 326 IAC 2-7 (Part 70) not applicable to the source.

D.1.2 Hazardous Air Pollutants (HAPs) [326 IAC 2-8-4]

- (a) The total usage of any single hazardous air pollutant (HAP) at the twenty one (21) spray paint booths shall be limited to less than 10 tons per twelve (12) consecutive month period with compliance determined at the end of each month. Compliance with this condition including insignificant activities shall limit the source-wide potential to emit a single HAP to less than 10 tons per twelve (12) consecutive month period with compliance determined at the end of each month.
- (b) The combined usage of all hazardous air pollutants (HAPs) at the twenty one (21) spray paint booths shall be limited to less than 25 tons per twelve (12) consecutive month period with compliance determined at the end of each month. Compliance with this condition. including the potential to emit of insignificant activities, shall limit the source-wide potential to emit total HAPs to less than 25 tons per 12 consecutive month period with compliance determined at the end of each month.

Compliance with these limitations shall make the requirements of 326 IAC 2-7 (Part 70) not

Swiss Plywood Corp. Page 24 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

applicable to the source.

D.1.3 Particulate-Matter (PM) [40 CFR 52 Subpart PI

Pursuant to 40 CFR 52 Subpart P, the PM from the twenty one (21) paint spray booths shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

 $E = 4.10 P^{0.67}$ where E = rate of emission in pounds per hour; and P = process weight rate in tons per hour

D.1.4 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for the spray paint facilities and their control devices.

Compliance Determination Requirements

D.1.5 Volatile Organic Compounds (VOC) and Hazardous Air Pollutants (HAPs)

Compliance with the VOC and HAP usage limitations contained in Conditions D.1.1 and D.1.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

D.1.6 VOC and HAP Emissions

Compliance with Conditions D.1.1 and D.1.2 shall be demonstrated within 30 days of the end of each month based on the respective total volatile organic compound, and single HAP and total HAP usages for the most recent twelve (12) month period.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

D.1.7 Particulate [326 IAC 6-3-2(d)]

Pursuant to and 326 IAC 6-3-2(d). particulate from the twenty one (21) spray paint booths. shall each be controlled by a dry filter, and the Permittee shall operate the dry filters in accordance with manufacturer's specifications.

D.1.8 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

Swiss Plywood Corp. Page 25 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

(c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.1.9 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1 and D.1.2, the Permittee shall maintain records in accordance with (1) through (6) below. Records maintained for (1) through (6) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC and HAP usage limits established in Conditions D.1.1 and D.1.2.
 - (1) The VOC and HAP content of each coating material and solvent used;
 - (2) The amount of coating material and solvent less water used on monthly basis.
 - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (3) The total VOC usage for each month;
 - (4) The total individual and combined HAP usage for each month;
 - (5) The weight of VOCs emitted for each compliance period; and
 - (6) The weight of total individual and combined HAPs emitted for each compliance period.
- (b) To document compliance with Condition D.1.8, the Permittee shall maintain a log of daily overspray observations. once per shift and weekly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C General Record Keeping Requirements, of this permit.

D.1.10 Reporting Requirements

A quarterly summary of the information to document compliance with Conditions D.1.1 and D.1.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Swiss Plywood Corp. Page 26 of 35
Tell City, Indiana OP No. F123-15136-00007
Permit Reviewer: AY/EVP

SECTION D.2

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]:

(b) One (1) woodworking operation identified as E22 with a maximum throughput of 4200 pounds per hour of wood, equipped with two (2) baghouses (identified as E22a & E22b) for particulate matter control and exhausting through stacks S38a and S38b, respectively.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.2.1 Particulate [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate emission rate from the woodworking operation shall not exceed 6.74 pounds per hour when operating at a process weight rate of 4,200 pounds per hour.

The pounds per hour limitation was calculated with the following equation:

Interpolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

 $E = 4.10 \ P^{0.67}$ where E = rate of emission in pounds per hour; and P = process weight rate in tons per hour.

Compliance with this limitation shall make the requirements of 326 IAC 2-2 (PSD) not applicable to the source.

D.2.2 PM10 Emission Limitation [326 IAC 2-8-4]

The total PM_{10} emissions from the woodworking operation shall not exceed 6.74 pounds per hour, which is equivalent to 29.52 tons per year. Therefore, the requirements of 326 IAC 2-7 do not apply.

D.2.3 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and its control device.

Compliance Determination Requirements

D.2.4 Particulate Control

In order to comply with Condition D.2.1 and D.2.2, the baghouses (E22a and E22b) for PM and PM10 control shall be in operation at all times that the woodworking operation is in operation.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

D.2.5 Visible Emissions Notations

- (a) Daily visible emission notations of the woodworking operations control device stack exhausts (S38a and S38b) shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or

Swiss Plywood Corp. Page 27 of 35
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.

- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

D.2.6 Baghouse Inspections

An inspection shall be performed each calender quarter of all bags controlling the woodworking. All defective bags shall be replaced.

D.2.7 Broken or Failed Bag Detection

In the event that bag failure has been observed:

- (a) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if there are no visible emissions or if the event qualifies as an emergency and the Permittee satisfies the emergency provisions of this permit (Section B- Emergency Provisions). Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (b) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B Emergency Provisions).

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.2.8 Record Keeping Requirements

- (a) To document compliance with Condition D.2.5, the Permittee shall maintain records of daily visible emission notations of each woodworking operations stack exhaust.
- (b) To document compliance with Condition D.2.6, the Permittee shall maintain records of the results of the inspections required under Condition D.2.6.
- (c) All records shall be maintained in accordance with Section C General Record Keeping Requirements, of this permit.

Swiss Plywood Corp. Page 28 of 35 Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

There are no specific reporting requirements applicable to these facilities.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT **OFFICE OF AIR QUALITY**

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) **CERTIFICATION**

Source Name:

Swiss Plywood Corp. 102 Main St., Tell City, Indiana 47586 Source Address:

Maili	ng Address: OP No.:	102 Main St., Tell City, Indiana 47586 123-15136-00007
	This certification	n shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.
	Please check wha	t document is being certified:
9	Annual Compliand	ce Certification Letter
9	Test Result (speci	fy)
9	Report (specify)	
9	Notification (speci	fy)
9	Affidavit (specify)	
9	Other (specify)	
	•	nformation and belief formed after reasonable inquiry, the statements and information i.e., accurate, and complete.
Sigi	nature:	
Prin	nted Name:	
Title	e/Position:	
Dat	e:	

Page 29 of 35 OP No. F123-15136-00007

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

COMPLIANCE BRANCH P.O. Box 6015 100 North Senate Avenue Indianapolis, Indiana 46206-6015 Phone: 317-233-5674 Fax: 317-233-5967

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) **EMERGENCY OCCURRENCE REPORT**

Source Name: Swiss Plywood Corp.

102 Main St., Tell City, Indiana 47586 Source Address: 102 Main St., Tell City, Indiana 47586 Mailing Address:

123-15136-00007 FESOP No.:

This form consists of 2 pages

Page 1 of 2

 ${f 9}$ This is an emergency as defined in 326 IAC 2-7-1(12)

CThe Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and

CThe Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

Page 30 of 35 OP No. F123-15136-00007

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _X , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:
Form Completed by: Title / Position: Date: Phone:

A certification is not required for this report.

Swiss Plywood Corp. Tell City, Indiana

Permit Reviewer: AY/EVP

Phone:

Page 31 of 35 OP No. F123-15136-00007

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

	FESOF	Quarterly Report		
Source Name: Source Address: Hailing Address: Source Address: Mailing Address: How Main St., Tell City, Indiana 47586 How Main St., Tel				
	Column 1	Column 2	Column 1 + Column 2	
Month	This Month	Previous 11 Months	12 Month Total	
Month 1				
Month 2				
Month 3				
Title	e / Position: nature:	nis quarter.		

Page 32 of 35 OP No. F123-15136-00007

Attach a signed certification to complete this report.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR MANAGEMENT COMPLIANCE BRANCH 100 North Senate Avenue P.O. Box 6015 Indianapolis, Indiana 46206-6015

FESOP Quarterly Report

Source Name: Sv	viss Plywood Corp.
-----------------	--------------------

Source Address: 102 Main St., Tell City, Indiana 47586 Mailing Address: 102 Main St., Tell City, Indiana 47586

FESOP No.: 123-15136-00007

Facilities: Spray paint booths (E1, E2, E3, E5, E6, E7, E9, E10, E11, E13, E14, E15, E17, E19,

E20, E21, E23, E24, E25, E26 and E28)

Parameter: Single and Combined Hazardous Air Pollutants (HAPs)

Limits: The total input usage of any single HAP, and total HAPs delivered to the applicators in

the twenty one (21) spray paint booths (identified as (E1, E2, E3, E5, E6, E7, E9, E10, E11, E13, E14, E15, E17, E19, E20, E21, E23, E24, E25, E26 and E28)) and during clean-up shall be limited to less than 10 and 25 tons per twelve (12) consecutive month

period with compliance determined at the end of each month, respectively.

Month	Total Usage This Month (tons) Total Usage Previ Months (tons			Total Usage 12 Months (tons)		
	Single HAP	Combined HAPs	Single HAP	Combined HAPs	Single HAP	Combined HAPs
Month 1						
Month 2						
Month 3						

YEAR: _____

No de	No deviation occurred in this quarter.					
	Deviation/s occurred in this quarter. Deviation has been reported on:					
	itted by:					
Title / Signa	Position: _ ture:					
9 3	_					

Page 33 of 35 OP No. F123-15136-00007

Date:	
Phone:	

Attach a signed certification to complete this report.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT

Source Name: Swiss Plywood Corp.

Source Address: 102 Main St., Tell City, Indiana 47586 Mailing Address: 102 Main St., Tell City, Indiana 47586

FESOP No.: 123-15136-00007

	Page 1 of 2
e submitted quarterly based on a calendar year.	Any deviation from the requirements,

This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

Months: _____ to ____ Year: ____

9 NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.

9 THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD

Permit Requirement (specify permit condition #)

Date of Deviation: Duration of Deviation:

Number of Deviations:

Probable Cause of Deviation:

Response Steps Taken:

Permit Requirement (specify permit condition #)

Date of Deviation: Duration of Deviation:

Number of Deviations:

Page 34 of 35 OP No. F123-15136-00007

Probable Cause of Deviation:	
Response Steps Taken:	

Page 35 of 35 OP No. F123-15136-00007

Page 2 of 2

	1 age 2 of 2	
Permit Requirement (specify permit condition #)		
Date of Deviation:	Duration of Deviation:	
Number of Deviations:		
Probable Cause of Deviation:		
Response Steps Taken:		
Permit Requirement (specify permit condition #)		
Date of Deviation:	Duration of Deviation:	
Number of Deviations:		
Probable Cause of Deviation:		
Response Steps Taken:		
Permit Requirement (specify permit condition #)		
Date of Deviation:	Duration of Deviation:	
Number of Deviations:		
Probable Cause of Deviation:		
Response Steps Taken:		
Form Completed By:		
, ,		
Title/Position:		
Date:		
Phone:		

Attach a signed certification to complete this report.

Indiana Department of Environmental Management Office of Air Quality

Addendum to the Technical Support Document (TSD) for a Federally Enforceable State Operating Permit (FESOP) Renewal

Source Name: Swiss Plywood Corp.

Source Location: 102 Main Street, Tell City, Indiana 47586

SIC Code: 2434, 2511, 2517 and 2599

County: Perry

Operation Permit No.: F123-15136-00007
Permit Reviewer: Adeel Yousuf /EVP

On October 14, 2002, the Office of Air Quality (OAQ) had a notice published in the Perry Co. News, Tell City, Indiana, stating that Swiss Plywood Corp. had applied for a Federally Enforceable State Operating Permit (FESOP) Renewal for the operation of a wood furniture and cabinet manufacturing plant. The notice also stated that OAQ proposed to issue a Federally Enforceable State Operating Permit Renewal for this operation and provided information on how the public could review the proposed FESOP Renewal and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this FESOP Renewal should be issued as proposed.

Upon further review, the OAQ has decided to make the following changes to the FESOP Renewal. Bolded language has been added and the language with a line through it has been deleted.

1. A general source phone number has been added to the permit. "County Status" has been deleted; it was not removed previously when replaced by "Source Location Status" in order to clarify when only portions of a county are non-attainment.

A.1 General Information [326 IAC 2-8-3(b)]

The Permittee owns and operates a stationary wood furniture and cabinet manufacturing plant.

Authorized individual: William Borders, **President**

Source Address: 102 Main Street, Tell City, Indiana 47586 Mailing Address: 102 Main Street, Tell City, Indiana 47586

General Source Phone: (812) 547-2366

SIC Code: 2434, 2511, 2517 and 2599

County-Source Location Status: Perry

County Status:

Source **Location** Status: Attainment for all criteria pollutants

Federally Enforceable State Operating Permit (FESOP)

Minor Source, under PSD Rules

Minor Source, Section 112 of the Clean Air Act

Section B

2. The general provisions; term of permit rule cite was added to B.3 Permit Term. In order to avoid confusion for renewals as to what "original" date IDEM is referring to, the following change has been made:

Swiss Plywood Corp. Page 2 of 9
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

B.3 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]

This permit is issued for a fixed term of five (5) years from the original **issuance** date **of this permit**, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

- 3. Since B.8 (c) Duty to Supplement and Provide Information already addresses confidentiality, the last sentence of (b) was revised to remove the statement about confidential information, and (c) was updated for clarity. Also, the condition was revised to change a rule reference. Subpart (c) references 326 IAC 17. This rule was repealed by the Air Pollution Control Board on January 26, 2000. The new rule reference has been added as follows:
- B.8 Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)] [326 IAC 2-8-5(a)(4)]
 - (a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit. or, for information claimed to be confidential, the Permittee may furnish such records directly to the U. S. EPA along with a claim of confidentiality.[326 IAC 2-8-4(5)(E)]
- (c) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1 When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.
- 4. The requirement to include emergencies in the Quarterly Deviation and Compliance Monitoring Report has been moved from B.15 to B.14. The statement at the end of Emergency Provisions B.14(b)(4) has been removed, because this is stated again in (f).

B.14 Emergency Provisions [326 IAC 2-8-12]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describes the following:

Swiss Plywood Corp. Page 3 of 9
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

(1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;

- (2) The permitted facility was at the time being properly operated;
- During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone No.: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section) or,

Telephone No.: 317-233-5674 (ask for Compliance Section)

Facsimile No.: 317-233-5967

Failure to notify IDEM, OAQ by telephone or facsimile within four (4) daytime business hours after the beginning of the emergency, or after the emergency is discovered or reasonably should have been discovered, shall constitute a violation of 326 IAC 2-8 and any other applicable rules. [326 IAC 2-8-12(f)]

(5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management Compliance Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.

Page 4 of 9 OP No. F123-15136-00007

Swiss Plywood Corp. Tell City, Indiana Permit Reviewer: AY/EVP

- (e) IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
 - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
 - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
 - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.
- 5. (c) has been removed from B.15 Deviations from Permit Requirements and Conditions, then revised and incorporated in B.14 Emergency Provisions.

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement

Page 5 of 9 OP No. F123-15136-00007

Permit Reviewer: AY/EVP

Swiss Plywood Corp.

Tell City, Indiana

of the permit.

(c) Emergencies shall be included in the Quarterly Deviation and Compliance Monitoring Report.

6. B.18 Permit Amendment or Revision has been revised to replace "should" with "shall" in (b).

B.18 Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

Any such application should shall be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

7. In order to be consistent with 326 IAC 2-8-15(a)(5) the rule cite has been revised in B.19(a)(5) B.19 Operational Flexibility. (b) has been removed, because this is a Part 70 requirement, but not a FESOP requirement.

B.19 Operational Flexibility [326 IAC 2-8-15]

(a) (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-8-15(b) through (d) and makes such records available, upon reasonable request, to public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-8-15(b)(2), (c)(1), and (d).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-8-15(a) and the following additional conditions:
 - (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
 - (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

(eb) Emission Trades [326 IAC 2-8-15(c)]
The Permittee may trade increases and decreases in emissions in the source, where the

Swiss Plywood Corp. Page 6 of 9
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).

- (dc) Alternative Operating Scenarios [326 IAC 2-8-15(d)]

 The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAQ or U.S. EPA is required.
- 8. B.22 (c)Transfer of Ownership or Operational Control rule cite has been corrected.
 - (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-110(b)(3)]
- 9. 326 IAC 2-1.1-7 specifies that nonpayment may result in revocation of the permit. This is not specified in 326 IAC 2-8; therefore, this rule cite is being added to B.23. Also, the section and phone number of who the Permittee can contact has been corrected in (c).
- B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16] [326 IAC 2-1.1-7]
 - (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-0425
 4320 (ask for OAQ, Technical Support and Modeling Section I/M & Billing Section), to determine the appropriate permit fee.

Section C

- 10. C.2 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour has been revised as follows.
- C.2 Particulate Emission Limitations For Manufacturing Processes with Process Weight Rates

 Less Than One Hundred (100) Pounds Per Hour [326 IAC 6-3-2(e)]

Pursuant to 326 IAC 6-3-2(e)(2), the allowable particulate emissions rate from any manufacturing process not exempt by 326 IAC 6-3-1 or already regulated by 326 IAC 6-3-2(b) through (d), and which has a maximum process weight rate less than 100 pounds per hour, shall not exceed 0.551 pounds per hour.

- C.2 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P1[326 IAC 6-3-2]
 - (a) Pursuant to 40 CFR 52 Subpart P, the allowable particulate matter emissions rate from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard. and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.
 - (b) Pursuant to 326 IAC 6-3-2(e)(2), the allowable particulate emissions rate from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.
- 11. C.8(e) Asbestos Abatements Projects has been revised to correct the rule cite.
- (e) Procedures for Asbestos Emission Control

The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-41, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.

Swiss Plywood Corp. Page 7 of 9
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

12. The following was added to C.10 Compliance Requirements to state what OAQ does when stack testing, monitoring, or reporting is required to assure compliance with applicable requirements.

C.10 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing. monitoring or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

- 13. C.19 (d) General Reporting Requirements has been revised to indicate all forms instead of the choice between quarterly or semi-annual.
 - (d) Unless otherwise specified in this permit, any quarterly all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. The report do All reports do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Section D

14. The following VOC language has been incorporated into D.1.5 to clarify what documentation is needed to determine compliance with the VOC and HAP limitations.

D.1.5 Volatile Organic Compounds (VOC) and Hazardous Air Pollutants (HAPs)

Compliance with the VOC and HAP usage limitations contained in Conditions D.1.1 and D.1.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer. by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

15. The following VOC record keeping requirements language has been incorporated into D.1.9 to clarify what records should be kept to demonstrate compliance with the VOC and HAP limits.

D.1.9 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1 and D.1.2, the Permittee shall maintain records in accordance with (1) through (6) below. Records maintained for (1) through (6) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC and HAP usage limits established in Conditions D.1.1 and D.1.2.
 - (1) The amount, and VOC and HAP content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) A log of the dates of use;
 - (2) The amount of coating material and solvent less water used on monthly basis.

Page 8 of 9 OP No. F123-15136-00007

- (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
- (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents.
- (3) The total VOC usage for each month;
- (4) The total individual and combined HAP usage for each month;
- (5) The weight of VOCs emitted for each compliance period; and
- (6) The weight of total individual and combined HAPs emitted for each compliance period.
- (b) To document compliance with Condition D.1.8, the Permittee shall maintain a log of daily overspray observations. once per shift and weekly inspections and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C General Record Keeping Requirements, of this permit.
- 16. Previously, the terms "particulate" and "particulate matter" were both used in the 326 IAC 6-3, but revisions were made to the rule which became effective on June 12, 2002 that included using the term "particulate" consistently in 326 IAC 6-3.

D.2.4 Particulate Matter (PM) Control

In order to comply with Condition D.2.1 and D.2.2, the baghouses (E22a and E22b) for PM and PM10 control shall be in operation at all times that the woodworking operation is in operation.

17. Additional information has been added to D.2.7(b) to describe when a failed unit will be shut down.

D.2.7 Broken or Failed Bag Detection

In the event that bag failure has been observed:

- (b) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation. or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B Emergency Provisions).
- 18. The first box on the Emergency Occurrence Report form was revised to include the word "working" in order to be consistent with 326 IAC 2-8-12(b)(5) and the Emergency Provision.

Swiss Plywood Corp. Page 9 of 9
Tell City, Indiana OP No. F123-15136-00007

Permit Reviewer: AY/EVP

 ${f 9}$ This is an emergency as defined in 326 IAC 2-7-1(12)

- The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
- The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Federally Enforceable State Operating Permit (FESOP) Renewal

Source Background and Description

Source Name: Swiss Plywood Corp.

Source Location: 102 Main Street, Tell City, IN 47586

County: Perry

SIC Code: 2434, 2511, 2517 and 2599

Operation Permit No.: F123-15136-00007 **Permit Reviewer:** Adeel Yousuf / EVP

The Office of Air Quality (OAQ) has reviewed a FESOP renewal application from Swiss Plywood Corp. relating to the operation of a wood furniture and cabinet manufacturing plant. Swiss Plywood Corp. was issued FESOP 123-6530-00007 on October 6, 1997.

Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

- (a) Twenty-one (21) spray paint booths identified as E1, E2, E3, E5, E6, E7, E9, E10, E11, E13, E14, E15, E17, E19, E20, E21, E23, E24, E25, E26 and E28 (each constructed prior to 1974). Each booth is equipped with conventional air spray guns, HVLP spray guns, and air-assisted airless spray guns for wood furniture coating, and is equipped with dry filters for particulate matter control, and each exhausting through stacks identified as following: S1 and S2 for E1; S3 and S4 for E2; S5 S7 for E3; S10 and S11 for E5; S12 and S13 for E6; S41 for E7; S17 and S18 for E9; S19 and S20 for E10; S21 and S22 for E11; S24 and S25 for E13; S26 for E14; S28 and S29 for E15; S31 and S32 for E17; S16 for E19; S34 for E20; S33 for E21; S35 for E23; S36 for E24; S37 for E25; S40 for E26; and S39 for E28.
- (b) One (1) woodworking operation identified as E22 with a maximum throughput of 4200 pounds per hour of wood, equipped with two (2) baghouses (identified as E22a & E22b) for particulate matter control and exhausting through stacks S38a and S38b, respectively.

Insignificant Activities

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Vessels storing lubricating oils, hydraulic oils, machining oils, and machining fluids;
- (b) Filling drums, pails or other packaging containers with lubricating oils, waxes, and greases.
- (c) Cleaners and solvents characterized as follows:
 - (1) having a vapor pressure equal to or less than 2 kPa, measured at 38°C, or

- (2) having a vapor pressure equal to or less than 0.7 kPa, measured at 20°C.
- (d) Water based adhesives that are less than or equal to 5% by volume of VOCs excluding HAPs.
- (e) Replacement or repair of electrostatic precipitators, bags in baghouses and filters in other air filtration equipment.
- (f) Paved and unpaved roads and parking lots with public access.
- (g) Purging of gas lines and vessels that is related to routine maintenance and repair of buildings, structures, or vehicles at the source where air emissions from those activities would not be associated with any production process.
- (h) Natural gas fired combustion sources with heat input equal to or less than 10 million British thermal units per hour: Five (5) natural gas fired heating ovens, identified as E4, E8, E12, E16 and E18, each rated at maximum heat input rate of 2.30 MMBtu/hr.

Existing Approvals

The source has been operating under the following previous approvals:

- (a) FESOP 123-6530-00007, issued on October 6, 1997.
- (b) First Significant Modification 123-9297-00007, issued on June 30, 1998.
- (c) First Administrative Amendment 123-10492-00007, issued on January 22, 1999.

All terms and conditions of previous permit issued pursuant to permitting programs approved into the state implementation plan have been either incorporated as originally stated, revised, or deleted by this permit. All previous registrations and permits are superseded by this permit.

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the FESOP Renewal be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete FESOP Renewal application for the purposes of this review was received on December 10, 2001. Additional information was received on August 7, 2002.

There was no notice of completeness letter mailed to the source.

Emission Calculations

See Appendix A of this document for detailed emissions calculations (four (4) pages).

Unrestricted Potential Emissions

This table reflects the unrestricted potential emissions of the source, excluding the emission limits that were contained in the previous FESOP.

Pollutant	Unrestricted Potential Emissions (tons/yr)
PM	4,515.22
PM-10	4,509.52
SO ₂	0.03
VOC	590.28
CO	4.23
NO _x	5.04

Note: For the purpose of determining Title V applicability for particulates, PM-10, not PM, is the regulated pollutant in consideration.

HAP's	Unrestricted Potential Emissions (tons/yr)
Methanol	greater than 10
Toluene	greater than 10
MEK	greater than 10
Xylene	less than 10
Methyl Isobutyl Ketone	less than 10
TOTAL	greater than 10

- (a) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of PM, PM-10 and VOC are equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of any single HAP is equal to or greater than ten (10) tons per year and the potential to emit (as defined in 326 IAC 2-1.1-1(16)) of a combination HAPs is greater than or equal to twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (c) Fugitive Emissions

Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 and since there are no applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive emissions are not counted toward determination of PSD and Emission Offset applicability.

Potential to Emit After Issuance

The source, issued a FESOP on October 6, 1997, has opted to remain a FESOP source, rather than apply for a Part 70 Operating Permit. The table below summarizes the potential to emit, reflecting all limits, of the emission units. Any control equipment is considered enforceable only after issuance of this Federally Enforceable State Operating Permit and only to the extent that the effect of the control equipment is made practically enforceable in the permit. Since the source has not constructed any new emission units, the source's potential to emit is based on the emission units included in the original FESOP. (F123-6530-00007; issued on October 6, 1997).

		Potential to Emit After Issuance (tons/year)						
Process/emission unit	PM	PM-10	SO ₂	VOC	CO	NO _X	HAPs	
Surface Coating (21 booths)	11.5	5.8	1	96.0 (3)	-	-	(1)	
Woodworking	29.52 ⁽²⁾	29.52 ⁽²⁾	-	-	-	-	-	
Insignificant Activities	1.38	0.88	0.03	2.28	4.23	5.04	negl.	
Total PTE After Issuance	42.4	36.2	0.03	98.28	4.23	5.04	< 10 (single) < 25 (total)	

- (1) Single HAP and total HAPs emissions from the twenty one (21) spray paint booths combined are limited to less than 10 and 25 tons per year, respectively.
- (2) Reflects the PM and PM10 emissions based on 326 IAC 6-3-2(e) allowable and 8760 hours of operation per year (assumes PM = PM10).
- (3) Based on limited VOC usage for surface coating operations which requires to limit the potential to emit of VOC to less than 100 tons per 12 consecutive month period such that the requirement of 326 IAC 2-7 shall not apply.

County Attainment Status

The source is located in Perry County.

Pollutant	Status		
PM-10	attainment		
SO ₂	attainment		
NO ₂	attainment		
Ozone	attainment		
CO	attainment		
Lead	attainment		

(a) Volatile organic compounds (VOC) are precursors for the formation of ozone.

Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Perry County has been designated as attainment or unclassifiable for ozone.

Federal Rule Applicability

There are no new federal rules applicable to the source during this FESOP renewal review process. The applicability determination that follows is based on that conducted for the original FESOP F123-6530-00007, issued on October 6, 1997.

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this source.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 63) applicable to this source since the source is not a major source of hazardous air pollutants pursuant to 40 CFR Part 63.2. The source shall limit coating material usage such that single and combined HAP emissions are limited to less than 10 tov and 25 tpy, respectively, making this a minor source of HAPs pursuant to 40 CFR Part 63.2.

State Rule Applicability - Entire Source

There are no new state rules applicable to the source during this FESOP review process. The applicability determination that follows is based on that conducted for original FESOP 123-6530-00007, issued on October 6, 1997.

326 IAC 2-2 and 40 CFR 52.21 (Prevention of Significant Deterioration, PSD)

The existing source was constructed prior to the August 7, 1980 rule applicability date. This source is not considered a major source because it is not one of the 28 listed source categories and it has the potential to emit after controls of less than 250 tons per year of any criteria pollutant. As a FESOP source, the total input usage of VOC shall be limited to less than 100 tons per year, and the control technology and related compliance requirements for particulates shall limit the potential to emit of PM_{10} (and PM) to less than 100 tons per year. Therefore, the requirements of 326 IAC 2-2 and 40 CFR 52.21 (Prevention of Significant Deterioration, PSD) shall not apply.

326 IAC 2-8-4 (FESOP)

This source is subject to 326 IAC 2-8-4 (FESOP). Pursuant to this rule, the following conditions shall apply:

(a) The total input usage of VOC delivered to the applicators in the twenty one (21) spray paint booths (identified as E1, E2, E3, E5, E6, E7, E9, E10, E11, E13, E14, E15, E17, E19, E20, E21, E23, E24, E25, E26 and E28) and during clean-up shall be limited to less than 100 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

- (b) The total input usage of any single HAP, and total HAPs delivered to the applicators in the twenty one (21) spray paint booths (identified as E1, E2, E3, E5, E6, E7, E9, E10, E11, E13, E14, E15, E17, E19, E20, E21, E23, E24, E25, E26 and E28) and during clean-up shall be limited to less than 10 and 25 tons per twelve (12) consecutive month period with compliance determined at the end of each month, respectively.
- (c) The total PM10 emitted from the woodworking operation and the spray paint booths shall be controlled at less than 100 tons per year by complying with the applicable control technology, work practices, monitoring and record keeping requirements.

Compliance with above conditions will limit the source-wide VOC, single HAP, and total HAPs emissions to less than 100. 10 and 25 tons per twelve (12) consecutive month period with compliance determined at the end of each month, respectively. Therefore, the requirements of 326 IAC 2-7 (Part 70) do not apply.

326 IAC 2-6 (Emission Reporting)

This source is located in Perry County which is not one of the specifically listed counties, nor does the source have the potential to emit CO, VOC, NOx, PM10 (including fugitive emissions), or SO₂ in amounts at or exceeding 100 tons per year. The potential to emit of all other regulated pollutants is less than 100 tons per year. Therefore, 326 IAC 2-6 does not apply.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

State Rule Applicability - Individual Facilities

On June 12, 2002, revisions to 326 IAC 6-3 (Particulate Emission Limitations for Manufacturing Processes) became effective; this rule was previously referred to as 326 IAC 6-3(Process Operations). As of the date this permit is being issued these revisions have not been approved by EPA into the Indiana State Implementation Plan (SIP); therefore, the following requirements from the previous version of 326 IAC 6-3 (Process Operations) which has been approved into the SIP will remain applicable requirements until the revisions to 326 IAC 6-3 are approved into the SIP and the condition is modified in a subsequent permit action.

326 IAC 6-3-2 (Process Operations)

Pursuant to 40 CFR 52 Subpart P, the particulate matter emissions from the surface coating facilities shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour

shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$
 where $E =$ rate of emission in pounds per hour; and $P =$ process weight rate in tons per hour

Under the rule revision, particulate from the surface coating facilities shall be controlled by a dry particulate filter and the Permittee shall operate the control device in accordance with manufacturer's specifications.

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)

The particulate from the woodworking operation shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$
 where $E =$ rate of emission in pounds per hour and $P =$ process weight rate in tons per hour

$$E = 4.10*(2.1)^{0.67} = 6.74$$
 lbs PM/hour

Based on the above equation, particulate emissions from the woodworking operation shall be limited to 6.74 pounds per hour.

Compliance calculation:

(2.25 tons PM/yr) * (yr/8,760 hrs) * (2,000 lbs/ton) = 0.51 lbs PM/hr

Actual lbs PM/hr (0.51 is less than the allowable lbs PM/hr (6.74), therefore the woodworking operation will comply with the requirements of 326 IAC 6-3-2.

The baghouses E22a and E22b shall be in operation at all times the wood working operation is in operation, in order to comply with this limit.

326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP))

This source is not subject to this rule. This rule applies to major sources of hazardous air pollutants (HAP) that were constructed or reconstructed after July 27, 1997. All the facilities at this source were constructed in 1974, therefore, 326 IAC 2-4.1 does not apply.

326 IAC 8-1-6 (General Reduction Requirements)

This rule applies to facilities located anywhere in the state that were constructed on or after January 1, 1980, which have potential volatile organic compound (VOC) emissions of 25 tons per year or more, and are not otherwise regulated by other provisions of Article 8. All coating facilities for Swiss Plywood Corp. were constructed in 1974. Therefore, rule 326 IAC 8-1-6 does not apply to the coating facilities of Swiss Plywood Corp.

326 IAC 8-2-12 (Wood Furniture and Cabinet Coating)

Pursuant to 326 IAC 8-2-1 (Applicability) and 326 IAC 8-2-12 (Wood Furniture and Cabinet Coating), facilities constructed in a listed county before November 1, 1980, which are located at a source with potential emissions of 100 tons per year or more of VOC, and which meet the criteria of 326

IAC 8-2-12(a), shall comply with the applicable requirements of 326 IAC 8-2-12. Facilities existing in specifically listed counties as of July 1, 1990, or that are newly constructed in any county after July 1, 1990, with actual emissions of greater than 15 pounds of VOC per day before add-on controls, shall likewise comply with the applicable requirements of 326 IAC 8-2-12.

The coating facilities for Swiss Plywood Corp., constructed prior to 1974 are not subject to this rule since these facilities are located in Perry County. which is a non-listed county. and has a limited potential to emit of VOC of less than 100 tons per year. Therefore, the requirements of this rule do not apply to these facilities. It is noted that these facilities, nonetheless, utilizes what would otherwise be compliant coating application methods.

326 IAC 8-6 (Organic Solvent Emission Limitations)

This rule applies to sources existing as of January 1, 1980, located in Lake and Marion Counties, as well as to sources commencing operation after October 7, 1974 and prior to January 1, 1980 that are located anywhere in the state, with potential VOC emissions of 100 tons per vear or more, and not regulated by any other provision of Article 8. The source has been in operation before October 7. 1974 and the potential emissions of VOC are less than 100 tons per year. Therefore, this rule does not apply to this source.

326 IAC 8-7 (Specific VOC Reduction Requirements for Lake. Porter, Clark and Floyd Counties)

The requirements of this rule apply to stationary sources located in Lake, Porter, Clark and Floyd

Counties that emit or have the potential to emit VOCs at levels equal to or greater than 25 tons per
year in Lake and Porter Counties; 100 tons per year in Clark and Floyd Counties; and to any
coating facility that emits or has the potential to emit 10 tons per year or greater in Lake, Porter,
Clark or Floyd County. The source is located in Perry County. Therefore, this rule is not applicable
to this source.

326 IAC 8-11 (Wood Furniture Coatings)

This rule applies to any person performing wood furniture manufacturing operations in Lake, Porter, Clark, or Floyd County, with the wood furniture manufacturing operations having potential emissions of VOC of 25 tons or more per year and occurring at a source classified with a listed Standard Industrial Classification (SIC) code. This rule is not applicable to this source since it is located in Perry County.

There are no other 326 IAC 8 rules that apply.

Testing Requirements

Compliance testing is not required of this source since the coating material usage and related VOC and volatile organic HAP emissions assume an emission factor of 2,000 pounds of pollutant emitted per ton of pollutant input to the coating operation, and the woodworking operations are controlled by two (2) baghouses with emissions after control well below the allowable particulate matter emission rate.

Compliance Requirements

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement

for a more or less continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

All compliance requirements from previous approvals were incorporated into this FESOP, except the frequency for visible emission notations for woohas been changed to once per shift.

Reason changed: Compliance monitoring conditions are in the permit in order to ensure continuous compliance with the requirements. Baghouse failure can occur suddenly; therefore monitoring should be more frequent than weekly or even daily in such cases where a source operates more than one shift per day. The OAQ believes that changing visible emissions notations to once per operating shift is a reasonable requirement. Therefore, the requirements to perform visible emissions notations have been changed from weekly to once per shift. The compliance monitoring requirements applicable to this source are as follows:

The compliance monitoring requirements applicable to this source are as follows:

- 1. The woodworking operation has applicable compliance monitoring conditions as specified below:
 - (a) Daily visible emissions notations of the woodworking operation baghouse stack exhausts shall be performed during normal daylight operations. A trained employee will record whether emissions are normal or abnormal. For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Preventive Maintenance Plan for this unit shall contain troubleshooting contingency and corrective actions for when an abnormal emission is observed. Failure to take response steps in accordance with Section C -Compliance Monitoring Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
 - (b) An inspection shall be performed each calender quarter of the baghouse controlling the woodworking operation when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors.

- (c) In the event that bag failure has been observed:
 - (1) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if there are no visible emissions or if the event qualifies as an emergency and the Permittee satisfies the emergency provisions of this permit (Section B- Emergency Provisions). Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
 - (2) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

These monitoring conditions are necessary because the baghouses for the woodworking operation must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-8 (FESOP).

- 2. The twenty one (21) spray paint booths (E1, E2, E3, E5, E6, E7, E9, E10, E11, E13, E14, E15, E17, E19, E20, E21, E23, E24, E25, E26 and E28) have applicable compliance monitoring conditions as specified below:
 - (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C Compliance Monitoring Plan Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
 - (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

(c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

These monitoring conditions are necessary because the spray paint booths must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-8 (FESOP).

Conclusion

The operation of this wood furniture and cabinet manufacture plant shall be subject to the conditions of the attached proposed FESOP No.: F123-15136-00007.

Appendix A: Emission Calculations

Company Name: Swiss Plywood Corp.

Address City IN Zip: 102 Main Street, Tell City, IN 47586

FESOP: 123-15136-00007
Reviewer: Adeel Yousuf / EVP
Date: September 4, 2002

Uncontrolled Potential Emissions (tons/year)

		Emissions Gene	rating Activity			
Pollutant					TOTAL	
	Coating	Operation		Combustion		
PM	11.50	4,503.34	1.00	0.38	4,516.22	
PM10	5.80	4,503.34	0.50	0.38	4,510.02	
SO2	0.00	0.00	0.00	0.03	0.03	
NOx	0.00	0.00	0.00	5.04	5.04	
VOC	588.00	0.00	2.00	0.28	590.28	
СО	0.00	0.00	0.00	4.23	4.23	
total HAPs	126.40	0.00	0.00	negl.	126.40	
worst case single HAP	(Methanol) 58.02	0.00	0.00	negl.	(Methanol) 58.02	
g					. ,	

Total emissions based on rated capacity at 8,760 hours/year.

Controlled Potential Emissions (tons/year)

Emissions Generating Activity								
Pollutant	Surface Coating	Woodworking Operation	Insignificant Activities	Natural Gas Combustion	TOTAL			
PM	11.50	2.25	1.00	0.38	15.1			
PM10	5.80	2.25	0.50	0.38	8.9			
SO2	0.00	0.00	0.00	0.03	0.0			
NOx	0.00	0.00	0.00	5.04	5.0			
VOC	96.00	0.00	2.00	0.28	98.28			
CO	0.00	0.00	0.00	4.23	4.23			
total HAPs	< 25	0.00	0.00	negl.	< 25			
worst case single HAP	(Methanol) < 10	0.00	0.00	neal.	(Methanol) < 10			

Total emissions based on rated capacity at 8,760 hours/year, after control.

Note: VOC emission of 2.0 tpy from Insignificant Activities and PM & PM10 emissions from surface coating operation of 11.50 and 5.80 tons per year, respectivley, are taken from the original FESOP 123-6530-00007.

Appendix A: Emission Calculations HAP Emissions Surface Coating Operations

Company Name: Swiss Plywood Corp.

Address City IN Zip: 102 Main Street, Tell City, IN 47586

FESOP: 123-15136-00007 Plant ID: 157-00037

Reviewer: Adeel Yousuf / EVP
Date: September 4, 2002

This table summerizes potential and limited VOC and HAP emissions for the surface coating operations.

	s potential and illilited v	Potential VOC	Potential HAP	Limited VOC	Limited HAP
Emission Unit	Maximum Rate	Emissions	Emissions	Emissions	Emissions
Suface Coating	units/hr	ton/year	ton/year	ton/year	ton/year
Booths					
E1	40.00	3.30	0.30		
E2	40.00	64.00	26.90		
E3	40.00	51.90	6.80		
E5	40.00	35.90	7.60		
E6	40.00	35.90	7.60		
E7	40.00	22.90	3.10		
E9	40.00	20.80	12.50		
E10	40.00	35.00	3.30		
E11	40.00	28.40	11.20		< 10.0 for single HAP
E13	40.00	35.6	8.2	< 96.0	< 25.0 for total HAPs
E14	40.00	23.7	4.7		
E15	40.00	23.7	4.7		
E17	40.00	23.7	4.7		
E19	40.00	22.9	3.1		
E20	40.00	22.9	3.1		
E21	40.00	22.9	3.1		
E23	40.00	22.9	3.1		
E24	40.00	22.9	3.1		
E25	40.00	22.9	3.1		
E26	40.00	22.9	3.1		
E28	40.00	22.90	3.10		

Total =	588.00	126.40	96.00	10.00	Single HAP
				25.00	Total HAPs

Notes:

VOC and HAPs emissions from surface coating booths are taken directly from the original FESOP (123-6530-00007), issued on October 6, 1997. See original FESOP permit application for a complete list of all VOCs and HAPs and their emission rates for each surface coating booth. The five (5) worst case HAPs are listed in the Technical Support Document (TSD).

Appendix A: Process Particulate Emissions

Company Name: Swiss Plywood Corp.

Address City IN Zip: 102 Main Street, Tell City, IN 47586

FESOP: 123-15136-00007 Plant ID: 157-00037

Reviewer: Adeel Yousuf / EVP Date: September 4, 2002

		Pote	ential Uncontrolled Er	nissions (tons/year)			
Baghouse ID	Process	No. of Units	Grain Loading per Actual Cubic Foot of Outlet Air	Air to Cloth Ratio Air Flow (acfm/ft²)	otal Filter Area (ft²)	Control Efficiency	Total (tons/yr)
E22a	Woodworking Operation	1	0.00100	18.0	3332.0	99.90%	2251.6
E22b	Woodworking Operation	1	0.00100	18.0	3332.0	99.90%	2251.6
Poshouse ID	Process	No. of Units	Grain Loading per	Air to Cloth Ratio Air		Control	Total
Baghouse ID							
bagnouse ID			Actual Cubic Foot of Outlet Air	Flow (acfm/ft²)	(ft²)	Efficiency	(tons/yr)
E22a	Woodworking Operation	1		, ,	(ft²) 3332.0	Efficiency 99.90%	(tons/yr)
	Woodworking Operation Woodworking Operation	1	of Outlet Air	18.0	,	,	. , ,
E22a E22b	. .	1	of Outlet Air 0.00100 0.00100	18.0	3332.0	99.90%	2.2

Allowable Emissions Calculation (per 326 IAC 6-3-2)

Woodworking Operations

Equation from 326 IAC 6-3-2: $E = 4.10 * (P^0.67)$ Process Wt. Rate (tons/hr), P = 2.10Allowable Emission Rate, E = 6.74 lbs/hr = 29.52 tons/yr

Methodology:

Potential Uncontrolled Emissions:

Emissions (tons/yr) = No. Units * Loading (grains/acf) * Air/Cloth Ratio (acfm/ft²) * Filter Area (ft²) * 1 lb/7,000 grains * 60 min/hr * 8760 hr/yr * 1 ton/2,000 lbs * 1/(1-Control Efficiency)

Controlled Emissions:

Emissions (tons/yr) = No. Units * Loading (grains/acf) * Air/Cloth Ratio (acfm/ft²) * Filter Area (ft²) * 1 lb/7,000 grains * 60 min/hr * 8760 hr/yr * 1 ton/2,000 lbs * 1/(1-Control Efficiency)

Appendix A: Emissions Calculations Natural Gas Combustion Only MM Btu/hr 0.3 - < 100

Company Name: Swiss Plywood Corp.

Address City IN Zip: 102 Main Street, Tell City, IN 47586

FESOP: 123-15136-00007

Plant ID: 157-00037

Reviewer: Adeel Yousuf / EVP Date: September 4, 2002

Heat Input Capacity Potential Throughput

MMBtu/hr MMCF/yr 11.50 100.7

Heat Input Capacity includes:

Five natural gas fired heating units, identified as E4, E8, E12, E16 and E18, each rated at maximum heat input rate of 2.30 MMBtu/hr.

Pollutant

	PM*	PM10*	SO2	NOx	VOC	СО
Emission Factor in lb/MMCF	7.6	7.6	0.6	100.0	5.5	84.0
				**see below		
Potential Emission in tons/yr	0.38	0.38	0.03	5.04	0.28	4.23

^{*}PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable PM10 combined.

Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03 (SUPPLEMENT D 3/98)

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

^{**}Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32